

Model DMM 120

Multimeter

4000-count Manual & Auto-Ranging



CE

4000-count Manual & Auto-Ranging Multimeter

- 600VAC/DC Voltmeter
- 10AAC/DC Ammeter
- Resistance to 40M Ω
- Continuity with Buzzer and Diode Test
- Capacitance, Frequency and % Duty Cycle
- Data HOLD and Back Light
- Auto Power OFF and Low Battery Indication
- Protective Industrial Grey Holster with Stand
- IEC/EN 61010 Safety Rated & CE Mark

4000-count Manual & Auto-Ranging Multimeter


ELECTRICAL SPECIFICATIONS	Model DMM 120
DC Volts	
Measurement Ranges	5 Ranges: 400mV, 4V, 40V, 400V, 600V
Accuracy* & Resolution	400mV: 0.5% ± 2cts – 0.1mV Resolution 4V: 0.5% ± 2cts – 1mV (0.001V) Resolution 40V: 0.5% ± 2cts – 10 mV (0.01V) Resolution 400V: 0.5% ± 2cts – 100 mV (0.1V) Resolution 600V: 0.5% ± 2cts – 1V Resolution
Input Impedance	10MΩ
AC Volts	
Measurement Ranges	5 Ranges: 400mV, 4V, 40V, 400V, 600V
Accuracy* & Resolution	400mV: 1.0% ± 4cts – 0.1mV Resolution 4V: 1.0% ± 4cts – 1mV (0.001V) Resolution 40V: 1.0% ± 4cts – 10mV (0.01V) Resolution 400V: 1.0% ± 4cts – 100mV (0.1V) Resolution 600V: 1.0% ± 4cts – 1V Resolution
Input Impedance	10MΩ
DC Amperes	
Measurement Ranges	6 Ranges: 400μA, 4mA, 40mA, 400mA, 4A, 10A
Accuracy* & Resolution	400μA: 1.2% ± 2cts – 0.1μA Resolution 4mA: 1.2% ± 2cts – 0.001mA Resolution 40mA: 1.2% ± 2cts – 0.01mA Resolution 400mA: 1.2% ± 2cts – 1mA (Resolution 4A: 1.2% ± 2cts – 1mA (0.001A) Resolution 10A: 1.2% ± 2cts – 10mA (0.01A) Resolution
AC Amperes	
Measurement Ranges	6 Ranges: 400μA, 4mA, 40mA, 400mA, 4A, 10A
Accuracy* & Resolution	400μA: 1.5% ± 4cts – 0.1μA Resolution 4mA: 1.5% ± 4cts – 0.001mA Resolution 40mA: 1.5% ± 4cts – 0.01mA Resolution 400mA: 1.5% ± 4cts – 1mA (Resolution 4A: 1.5% ± 4cts – 1mA (0.001A) Resolution 10A: 1.5% ± 4cts – 10mA (0.01A) Resolution
Resistance (Ohms)	
Measurement Ranges	7 Ranges: 40Ω, 400Ω, 4000Ω, 40kΩ, 400kΩ, 4MΩ, 40MΩ
Accuracy* & Resolution	40Ω: 1.0% ± 3cts – 0.01Ω Resolution 400Ω: 1.0% ± 3cts – 0.1Ω Resolution 4000Ω: 1.0% ± 3cts – 1Ω Resolution 40kΩ: 1.0% ± 3cts – 0.01kΩ Resolution 400kΩ: 1.0% ± 3cts – 0.1kΩ Resolution 4MΩ: 1.0% ± 3cts – 0.001MΩ Resolution 40MΩ: 1.0% ± 3cts – 0.01MΩ Resolution

4000-count Manual & Auto-Ranging Multimeter

Continuity	
Measurement Range	0 to 400Ω Range with Buzzer <100Ω Response time <10ms, 500VAC/DC PTC Protection
Diode Test	
Measurement Range	0 to 4.000V
Capacitance	
Measurement Ranges	5 Ranges: 40nF, 400nF, 40μF, 100μF
Accuracy* & Resolution	40nF: 3.0% ± 3cts – 0.01nF Resolution 400nF: 3.0% ± 3cts – 0.1nF Resolution 4μF: 3.0% ± 3cts – 0.001μF Resolution 40μF: 3.0% ± 3cts – 0.01μF Resolution 100μF: 3.0% ± 3cts – 0.1μF Resolution
Frequency (Hz)	
Measurement Ranges	6 Ranges: 40Hz, 400Hz, 4000Hz, 40kHz, 400kHz, 4MHz
Accuracy* & Resolution	40Hz: 0.2% ± 2cts – 0.01Hz Resolution 400Hz: 0.2% ± 2cts – 0.1Hz Resolution 4000Hz: 0.2% ± 2cts – 1Hz Resolution 40kHz: 0.2% ± 2cts – 0.01kHz Resolution 400kHz: 0.2% ± 2cts – 0.1kHz Resolution 4MHz: 0.2% ± 2cts – 0.01MHz Resolution
Duty Cycle (%)	
Measurement Range	0.1 to 99.9%, Accuracy 1% ± 3cts
Other Functions	
Data Hold	Yes – Dedicated “DATA HOLD” push-button (Yellow)
Back-Light	Yes – Press Data Hold push-button for 2 seconds
Auto-Range & Manual Range	Yes – Auto-Range with Manual selection through “RANGE” button (Grey)
Over-Range Indication	Yes – “OL” displayed if Over-Range
Auto-OFF	Yes – Auto-OFF with user over-ride to disable.
GENERAL SPECIFICATIONS	
Model DMM 120	
Display	4000-count 3¾ Digit LCD with backlight – “OL” Displayed for Over-Range
Operating Temperature & %RH	32° to 104°F (0° to 40°C), 80% RH max non-condensing
Storage Temperature & %RH	14° to 122°F (-10° to 50°C), 80% RH max non-condensing, battery removed
Altitude	6000 ft (2000m)
Range Selection	Auto-Ranging and Manual selection by “RANGE” push-button (Grey Button). “SELECT” push-button (Blue Button) for additional function selection: Hz/Duty Cycle and Ω/Diode/Continuity/Capacitance
Power Supply	2 Batteries – 1.5V type AA (LR6)
Battery Power Management	Low Battery Indicator on LCD Auto-Off after 30 minutes to conserve battery power
Fuse	500mA, 250V (5x20mm)
Holster	Grey color (dirt resistant) soft protective holster with stand
Dimensions & Weight	1.38 x 3.07 x 5.84” (35 x 78 x 152mm) - 11.8 oz (330g) with holster
Warranty	One Year
Safety	
Safety Standards	IEC/EN 61010 – 600V Cat. II and 300V Cat. III, CE mark

NOTE: * Accuracy given @ 23°C ± 5°C, 75% RH max

4000-count Manual & Auto-Ranging Multimeter



Multimetrix®

CHAUVIN ARNOUX Group

USA, Canada, North, Central &

South America, Australia & New Zealand:

CHAUVIN ARNOUX INC.

15 Faraday Drive
Dover, NH 03820, USA

Tel: (603) 749-6434

Fax: (603) 742-2346

www.multimetrix.us

Ordering Information

4000-count Multimeter Model DMM 120 Catalog Number: MMX-DMM120

Includes: Multimeter DMM 120 – Grey Rubber Holster - 1 x Lead Set with Needle Point Test Probe (Red & Black) - 2 x 1.5V AA Batteries - User Manual

Optional Accessories: Carry Case – Accessory No. 20 – Cat. MMX-ACC20.

Soft padded carrying case, with compartment for lead storage, belt loop and attachment ring. Front flap with Velcro® closure. For DMMs MMX 110/120/140 and X1000.

*Specifications and Prices are subject to change without notice.
Consult Factory before ordering.*